

Amendments to the Claims:

1. (Currently amended) A mobile communication station ~~for communicating with other devices~~ including a camera and having a body having a longest dimension along a first axis, the body comprising two portions which are mechanically coupled to each other by a linkage that permits rotation of one of the portions relative to the other about an axis substantially parallel to the said first axis and prevents rotation of each portion relative to the other about other axes, one of said portions having a grip for being gripped by a user during use of the communication station, the grip having a first compact configuration and a second configuration in which the grip is expanded relative to the first configuration to improve the grip of the user on the communication station when the grip is in the second expanded configuration.
2. (Currently amended) A mobile communication station as claimed in claim 1, wherein ~~the other of said portions is a body portion to which the grip is attached and with respect to which the grip is movable~~ with respect to the body of the mobile communication station.
3. (Currently amended) A mobile communication station as claimed in claim 2, wherein the body ~~portion~~ houses operational components of the communication station.
4. (Currently amended) A mobile communication station as claimed in claim 3, wherein the body ~~portion~~ includes the camera.
5. (Currently amended) A mobile communication station as claimed in claim 3, wherein user input and/or output components of the communication station are exposed on the surface of the body ~~portion~~.
6. (Currently amended) A mobile communication station as claimed in claim 2, wherein the grip is rotatable relative to the body ~~portion~~.

7. (Currently amended) A mobile communication station as claimed in claim 4, wherein the grip is rotatable relative to the body ~~portion~~ about an axis substantially parallel to the direction in which the camera points, so as to project from the body ~~portion~~.
8. (Currently amended) A mobile communication station as claimed in claim 4, wherein the grip is rotatable relative to the body ~~portion~~ about an axis substantially perpendicular to the direction in which the camera points, so as to project from the body ~~portion~~.
9. (Previously presented) A mobile communication station as claimed in claim 8, wherein in at least one rotational position the grip extends continuously from the body in the direction of the axis of rotation of the grip.
10. (Currently amended) A mobile communication station as claimed in claim 2, wherein the grip is slidable relative to the body ~~portion~~.
11. (Currently amended) A mobile communication station as claimed in claim 1, wherein the grip has a core portion and at least one outer wall movable away from the core portion, and wherein when ~~[[in]]~~ moving from the first compact configuration to the second expanded configuration the at least one outer ~~or each~~ wall is moved linearly away from the core portion.
12. (Original) A mobile communication station as claimed in claim 1, wherein in the mobile communication station is capable of operating as a mobile telephone.
13. (Currently amended) A mobile communication station as claimed in claim 12, the mobile communication station is capable of sensing relative motion of at least a part of the grip ~~portion~~ and another part of the mobile communication station, and in response switching from a first operating mode to a second operating mode.

14. (Previously presented) A mobile communication station as claimed in claim 1, wherein user input and/or output components of the communication station are exposed on the surface of the grip.
15. (Currently amended) A mobile communication station as claimed in claim 14, wherein the grip ~~portion~~ is movable relative to the direction in which the camera points so as to be capable of adopting a position in which the user input and/or output components of the communication station are exposed on the surface of the grip face in substantially the opposite direction to that in which the camera points.
16. (Original) A mobile communication station as claimed in claim 1, wherein changing the configuration of the grip from the first compact configuration to the second expanded configuration makes available an additional user interface for controlling the operation of the mobile communication station.
17. (Original) A mobile communication station as claimed in claim 1, wherein the grip houses operational components of the mobile communication station.
18. (Original) A mobile communication station as claimed in claim 17, wherein the grip is electrically connected to the main body of the mobile communication station.
19. (Cancelled)
20. (Previously presented) A mobile communication station as claimed in claim 1, wherein one of the portions includes a camera.
21. (Previously presented) A mobile communication station as claimed in claim 20, wherein the other of the portions includes a display.
22. (Original) A mobile communication station as claimed in claim 1, including gaming or editing functions.
23. (Canceled)

24. (New) A mobile communication station as claimed in claim 11, wherein the at least one wall is moveable away from the core portion in a direction substantially perpendicular to the first axis.
25. (New) A method comprising: providing a mobile communication station including a camera and having a body having a longest dimension along a first axis, the body comprising two portions which are mechanically coupled to each other by a linkage that permits rotation of one of the portions relative to the other about an axis substantially parallel to the said first axis and prevents rotation of each portion relative to the other about other axes, one of said portions having a grip configured to be gripped by a user during use of the communication station, the grip having a first compact configuration and a second configuration in which the grip is expanded relative to the first configuration to improve the grip of the user on the communication station when the grip is in the expanded configuration.
26. (New) A method as claimed in claim 25, wherein the grip has a core portion and at least one outer wall movable away from the core portion, and wherein when moving from the first compact configuration to the second expanded configuration the at least one outer wall is moved linearly away from the core portion.
27. (New) A method as claimed in claim 26, wherein the at least one wall is moveable away from the core portion in a direction substantially perpendicular to the first axis.